



PRODUCT SPECIFICATION

GENERAL

FINISH:	Plaster	GROSS WEIGHT:	To Be Advised
MAIN MATERIAL:	Plaster	CLASS:	cETLus (Class I)
DIMENSIONS:	H: 220mm W: 133mm D: 90mm H: 8.66" W: 5.24" D: 3.54"	LISTING LOCATION:	Dry
INSTALLATION ORIENTATION:	Wall Mount - Vertical	FITTING METHOD:	3x2" Switch Box, 1/2" Stub Mount or 4" Octagon Box
CUT OUT HOLE:	Not Applicable	ADA COMPLIANT:	Yes
RECESS DEPTH:	Not Applicable	IC RATING:	Not Applicable
FIRE RATING:	Not Applicable	VOLTAGE:	Mains 120 (V)
CABLE LENGTH:	Not Applicable		


LAMP

LIGHT SOURCE:	High Power LED	MACADAM ELIPSE:	To Be Advised
MAXIMUM WATTAGE:	2 x 3W	UGR:	Not Applicable
MAXIMUM LAMP LENGTH:	Not Applicable	BEAM ANGLE:	Not Applicable
LAMP INCLUDED?	Yes (Integral)	TILT ADJUSTMENT ANGLE:	Not Applicable
DELIVERED LUMENS:	327 (lm)	ROTATION ADJUSTMENT ANGLE:	Not Applicable
COLOR TEMP:	3000 (K)	AVERAGE LIFESPAN:	60,500 (Hrs)
CRI:	80	L70:	To Be Advised
R9:	14.0		


ELECTRICAL

SWITCHED:	No	SUPPLY FREQUENCY:	50/60 (Hz)
DIMMABLE:	No	DRIVER / BALLAST VOLTAGE:	100-277 (V)
DIMMING METHOD:	Not Applicable	DRIVER AVERAGE LIFESPAN:	50,000 (Hrs)
DRIVER OUTPUT CURRENT:	700 (mA)	EFFICACY:	59.56 (lm/w)
DRIVER OUTPUT VOLTAGE:	Not Applicable	DRIVER / BALLAST INCLUDED?	Yes (Integral)

ADDITIONAL INFORMATION



THIS PRODUCT CAN BE SPRAY PAINTED



BOX QUANTITY X6

PRODUCT ELEVATIONS

