## OSCA ROUND PENDANT

# astro

#### GENERAL

LOCATION: Interior
CLASS: CULus (Class 1)

LOCATION RATING: Dry
DRIVER REQUIRED: Mains 120V

INSTALLATION ORIENTATION: Ceiling Mount FITTING METHOD: 4" Octagon Box

MAIN MATERIAL: Plaster

 DIMENSIONS (mm):
 H: 2033 Ø: 110

 DIMENSIONS (inch):
 H: 80 Ø: 4.33

CUT OUT HOLE (mm/inch): RECESS DEPTH (mm/inch): FIRE RATING: -

CABLE LENGTH (mm/inch): 1800/70.87

GROSS WEIGHT (lb): 5.43

ADA COMPLIANT: Yes - if installed in compliance

with ADA 307.4

IC RATING:

#### LAMP

LIGHT SOURCE: E26/Medium WATTAGE: 23W Max

RECOMMENDED LAMP: 12W Max LED E26/Medium

LAMP INCLUDED: No MAXIMUM LAMP LENGTH (mm/inch): 130

LUMINOUS FLUX (Im):Lamp DependentCOLOUR TEMP (K):Lamp DependentCRI (Ra):Lamp DependentMACADAM ELLIPSE:Lamp Dependent

TILT ADJUSTABLE ANGLE (°): ROTATION ADJUSTABLE ANGLE (°): -

LIFETIME (hrs): Lamp Dependent
BEAM ANGLE (°): Lamp Dependent

#### **ELECTRICAL**

SWITCHED: No DIMMABLE: Yes

DIMMING METHOD: Lamp Dependent

SUPPLY FREQUENCY (Hz): DRIVER/BALLAST VOLTAGE (V): DRIVER LIFETIME (hrs): -

EFFICACY (Im/W): Lamp Dependent

### ADDITIONAL INFORMATION:

SHADE INCLUDED: SHADE/DIFFUSER MATERIAL: SHADE/DIFFUSER FINISH -

F MARK: Suitable for mounting

on flammable materials



CODE: 1252019 FINISH: PLASTER

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED. ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS, AND ALL RIGHTS TO SUCH DESIGNS AND IMAGERY ARE EXPRESSLY RESERVED.

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.



